

# TITAN LED

LIGHTING SOLUTIONS

WWW.TITANLED.NET

Product Specification Sheet

Hennessy Series

## 75 Watt Shoebox



Heavy Duty Driver  
Quick Connects

### Features: Drive Current 832 mA

- 28 high power Lumileds Luxeon LEDs
- Driver access hinged panels
- Driver quick connect adaptors
- Inventronics high efficiency, IP67 Driver
- Proprietary optics - 80° or 120° Diffusion light output
- Titan proprietary 4 bolt knuckle adaptor included
- Titan proprietary extruded aluminum heat sink
- ACC technology - Active Chamber Cooling
- No hazardous mercury or toxic chemicals
- Vibration and shock resistant
- No ultra violet
- Instant on/off, No ballast required
- USA Flame retardant polycarbonate lens
- Constant current design
- >65% savings in energy over MH & HPS lighting
- No flickering
- Greater than 96% recyclable
- UL Listing PENDING
- Photocell/Occupancy sensor Option
- Proudly Made in the United States of America

Attention: All specifications are subject to change without notice.

Lumen Output:	8,100 lm (Day White)
Wattage:	75Watts
Kelvin:	Day White (5,700K)
CRI:	79
Power Factor:	.99
THD:	6% @ 120V - 14% @ 277V
Dimensions:	16 5/8" L x 16 1/8" W x 7 1/4" H
Lighting Angle:	80° or 120° Diffusion Wide Angle
LED Count:	28 High Power - (Lumileds Luxeon LEDs)
Mounting:	Titan LED 4 bolt knuckle adaptor
Dimming:	0 - 10V / Range 10% - 100%
Sensor Option:	LV Occupancy & Photo Hybrid
Insitu. Diode temperature:	58.9°C
Max. Ambient Peak temperature:	-40 to 149° F / -40 to 65° C
Replaces:	200 Watt MH/HPS
Working Voltage:	120 - 277 V A/C
Net Weight:	17.65 lbs / 8.0 kg
Life Hours:	125,000 Hours
Warranty:	6 Years

### PRODUCT SKU #

**61BR-1P-28-9-80** Day White 80°

**61D-BR-1P-28-9-80** Day White 80°



Hennessy Series Luminaire Profile



4 bolt knuckle  
Tenon adaptor

**ACC** Technology™



**125,000**  
Lifetime Hours

**6** YEAR  
WARRANTY

**TITAN LED** 4590 Ish Drive, Unit # 100, Simi Valley, CA. 93063

Phone: (805) 523-7500 Fax: (805) 523-7502

Images and Information are Property of Titan LED Inc. 2015 and may only be used by permission.